

NFSU



**National Forensic
Sciences University**

Knowledge | Wisdom | Fulfillment
An Institution of National Importance

NFSU/ENGG/SBFDean's/washroom/renovation/ 163 /2024

National Forensic Sciences University
Gujarat State, Sector-9, Nr. DFS
Office,
Gandhinagar-382007
Date: 12/07/2024

Sub: **Quotation** for "Repair and Renovation work for SBF first floor washroom opp. Dean's Cabin at NFSU, Gandhinagar."

Dear Shri,

This University is in the process of Repair and Renovation work for SBF first floor washroom opp. Dean's Cabin at NFSU, Gandhinagar. as per the tentative specifications attached herewith. You are requested to send the quotation for this work on or before Dtd.

19/07/2023, (17:00 hours.)

1. Quotation will be accepted at our below mentioned address by courier/ speed post up to **19/07/2023, (17:00 hours.)**
2. Rate must be quoted inclusive of all taxes and work, as per specifications attached.
3. The bidder shall enclose copy of PAN card and GST no. along with the bid (Mandatory) otherwise bid shall be consider as null and void, and should attach work orders of same kind of work previously done.
4. Quotation will be valid up to **Six months** from the last date of submission of Quotation.
5. Quotation should be addressed to

**Campus Director
National Forensic Sciences University
Sector -9, Near DFS Office,
Gandhinagar-382 007**

6. Quotation should be sent by **Courier/Registered post/Speed Post/ in Person.**
7. Quotation should be sent in a **sealed** envelope.
8. On the top of the left corner of the envelope, the following may be specially mentioned.

Our reference No.

Quotation for Repair and Renovation work for SBF first floor washroom opp. Dean's Cabin at NFSU, Gandhinagar.

If the above details are not mentioned on the top of envelop, quotation is likely to be ignored.

9. Right to accept or reject any quotation without assigning any reason there of remains with the University.
10. All bidders are cautioned that offer form/ Quotation containing any condition and/or deviation from the contractual terms and conditions, specifications, quoting/offering rates/ prices in different manner than specified in the offer form/ Quotation and/or any other requirements of the Quotation shall make the Quotation liable to for outright rejection and shall be considered as no -responsive for all practical purposes. The decision of the University in this regard shall be final and binding to the bidders.

Campus Director

National Forensic Sciences University
Gandhinagar

National Forensic Sciences University Quotation/ Offer Letter

Name of Work: "Repair and Renovation work for SBF first floor washroom opp. Dean's Cabin at NFSU, Gandhinagar."

The **Specification and Quantity** is specified as below:

Sr. No.	Item Description	Quantity	Unit	Rate	Amount
1.	Dismantling tile work in floors and roofs laid in cement mortar including stacking material within 50 metres lead.	28.1	Sqm		
2.	Demolishing R.C.C. work manually/ by mechanical means including stacking of steel bars and disposal of unserviceable material within 50 metres lead as per direction of Engineer - in- charge	1.42	Cmt.		
3.	Dismantling W.C. Pan of all sizes including disposal of dismantled materials i/c malba all complete as per directions of Engineer-in-Charge.	01	No.		
4.	Providing and laying water proofing treatment in sunken portion of WCs, bathroom etc, by applying: <ul style="list-style-type: none"> First layer of slurry of cement at the rate of 0.488 KG per square metre mixed with waterproofing cement compound at the rate of 0.253 KG per square metre. This layer will be allowed to air cured for 4 hours. Second layer of slurry of cement At the rate of 0.242 KG per square metre mixed with waterproofing cement compound at the rate of 0.1 26 KG per square metre. This layer will be allowed to air cure for 4 hours. Followed with water curing for 48 hours. 	4.64	Sqm		
5.	Providing and laying cement Concrete in returning walls, including attached plaster, columns, piers, abutments, pillars, post, straps, buttresses, string or lacing courses, parapets, coping, bed blocks, anchor blocks, plane, windowsills, fillets, sunken Floor, etc up to floor 5 level, excluding the cost of Centering, shuttering and finishing: <ul style="list-style-type: none"> 1:1.5:3 (1 part of cement: 1.5 part of coarse sand (zone -3) derived from natural sources: 3 graded stone aggregate 20mm nominal size derived from natural sources) 	1.42	Cmt		
6.	Providing and laying vitrified floor tiles in different sizes (thickness to be specified by the manufacturer) with water absorption less than 0.08% and conforming to IS: 15622, of approved make, in all colour and shades, laid on 20mm thick cement mortar 1:4 (1 cement : 4 coarse sand), jointing with grey cement slurry @ 3.3 kg/ sqm including grouting the joints with white cement and matching pigments etc., complete. Glazed Vitrified Matt/antiskid tiles. Size : 600mmx600mm	4.64	Sqm		
7.	Providing and fixing white vitreous china pedestal type water closet (European type W.C pan) with seat and lid, 10 litre low level white PVC flushing cistem, including flush pipe, with manually controlled device (handle lever), conforming to IS 7231, with all fittings and fixtures complete, including cutting and making good the walls and floors wherever required.	01	No.		

	<ul style="list-style-type: none"> W.C. pan with ISI marked white solid plastic seat and lid 				
8.	<p>Providing and fixing 1st quality ceramic glazed floor tiles conforming to</p> <p>IS : 15622 (thickness to be specified by the manufacturer) of approved</p> <p>make in all colours, shades except burgundy, bottle green, black of any</p> <p>size as approved by Engineer-in-Charge in skirting, risers of steps and</p> <p>dados over 12 mm thick bed of cement Mortar 1:3 (1 cement: 3 coarse sand) and jointing with grey cement slurry @ 3.3kg per sqm including pointing in white cement mixed with pigment of matching shade</p> <p>complete.</p>	23.46	Sqm.		
9.	<p>Kota stone slab flooring over 20 mm (average) thick base laid over and</p> <p>jointed with grey cement slurry mixed with pigment to match the shade</p> <p>of the slab, including rubbing and polishing complete with base of cement</p> <p>mortar 1 : 4 (1 cement : 4 coarse sand) :</p> <ul style="list-style-type: none"> 25 mm thick 	0.5	Sqm.		
10.	<p>Grouting the joints of flooring tiles having joints of 3 mm width, using</p> <p>epoxy grout mix of 0.70 kg of organic coated filler of desired shade</p> <p>(0.10 kg of hardener and 0.20 kg of resin per kg), including filling /</p> <p>grouting and finishing complete as per direction of Engineer-in-charge.</p> <ul style="list-style-type: none"> Size of Tile 600x600 mm 	4.64	Sqm.		
Total Cost					


Civil Engineer

Sign and Seal of the Bidder